

Sony DSC-W300



1371109384.jpg



Dimensions (Approx.) : 3 11/16 x 2 5/16 x 1 1/16" (94.3mm x 59.0mm x 26.8mm) Weight (Approx.) : Approx. 5.5 oz (156g) Docking Station : Yes, via optional HD Cyber-shot® Station (CSS-HD2). LCD : 2.7"1 (230K Pixels) Clear Photo LCD Lens Construction : 6 Elements in 5 Groups(including 3 aspheric elements) Lens Type : Carl Zeiss® Vario-Tessar® Microphone/Speaker : Yes / Yes Viewfinder : Optical Imaging ...

??????? : ??? ????????

????:

??????????? ???:

????????? ??? ? ???:

???? ?? ???????:

???? ?? ???????:

????: 8748,16 ?.

???? ?? ??????: 8748,16 ?.

?????:

????? ??????:

[??????? ?????? ?? ????? ??????](#)

?????????

Dimensions (Approx.) : 3 11/16 x 2 5/16 x 1 1/16" (94.3mm x 59.0mm x 26.8mm)

Weight (Approx.) : Approx. 5.5 oz (156g)

Docking Station : Yes, via optional HD Cyber-shot® Station (CSS-HD2).

LCD : 2.7"1 (230K Pixels) Clear Photo LCD

Lens Construction : 6 Elements in 5 Groups(including 3 aspheric elements)

Lens Type : Carl Zeiss® Vario-Tessar®

Microphone/Speaker : Yes / Yes

Viewfinder : Optical

Imaging Device : 1/1.7" Super HAD™ CCD

Megapixel : 13.6 MP

Recording Media : 15MB7 internal Flash Memory, optional Memory Stick Duo™ Media, optional Memory Stick PRO Duo™ Media

Battery Capacity : 3.6V, 960 mAh

Battery Type : Lithium-Ion NP-BG1

Flash Mode(s) : Auto, Flash On, Flash Off, Slow Synch

Limited Warranty Term : 1 Year Parts & Labor

Burst Mode : Yes - 100 shots, 1.9 FPS (all resolutions); 5.0fps (using Extra High-speed Burst - 3 megapixel only)

Color Mode(s) : Normal, Vivid, Real, Black & White, Sepia

Date/Time Stamp : No/ No

Dynamic Range Optimizer : Standard & Advanced

Erase/Protect : Yes/Yes

Image Stabilization : Yes

Media/Battery Indicator : Yes/Yes

Memory Stick PRO™ Media Compatibility : Tested to support up to 16GB7; Memory Memory Stick PRO Duo™ Media capacity; does not support Access Control security function.

Red-Eye Reduction : Yes (On/Off all modes)

Scene Mode(s) : Beach, Extra High-speed Burst, Extra High Sensitivity6, Fireworks, Landscape, Snow, Soft Snap, Twilight, Twilight Portrait, Movie, High Sensitivity, Smile Shutter, Underwater

Self Timer : Yes (10 seconds, 2 seconds, Off)

Still Image Mode(s) : Normal, Burst, Bracket

White Balance : Automatic, Cloudy, Daylight, Fluorescent 1, Fluorescent 2, Fluorescent 3, Incandescent, Flash, One Push

AF Illuminator Light : Auto / Off, (W:Approx. 3.0m , T:Approx. 2.0m)

In-Camera Editing : Trimming, Red Eye Correction, Soft Focus, Partial Color, Fisheye Lens, Cross Filter, Retro, Radial Blur, Unsharp Masking, Happy Face

Movie Mode(s) : MPEG VX Fine(640x480 at 30fps) (MPEG VX Fine requires Memory Stick PRO Duo™ Media, MPEG VX Standard(640x480 at 16fps), Presentation(QVGA, 320 x 240, Approx.8.3fps)

Multi-Pattern Measuring : Yes

PictBridge Compatible : Yes

Power Save Mode : Yes (after approx. 3 min. of inactivity)

Real Imaging Processor™ Technology : BIONZ™

35mm Equivalent : 35 - 105mm

Aperture Range : Auto(f2.8-f16) / Program Auto(f2.8-f16)

Digital Zoom : 0-2.0X (Precision)

Exposure Compensation : Plus / Minus 2.0EV, 1 / 3EV step

Face Detection : Yes - recognizes up to 8 faces.

Filter Diameter : 74mm (with Adapter Ring)

Focal Length : 7.6-22.8mm

Focus : 9-Area Multi-Point AF, Center AF, Spot AF, Semi manual(0.5m/ 1.0m/ 3.0m/ 7.0m/ Unlimited Distance)

Macro Mode : Auto Macro / Macro Mode

Minimum Focus Distance : W:Approx. 1 15/16"(5cm) to Infinity, T:Approx. 13 3/8"(34cm) to Infinity

Optical Zoom : 3X

Shutter Speed : Auto(1/4 - 1/2,000) / Program Auto(1"- 1/2,000) / Manual(30"- 1/1,000)

Total Zoom : 6X

BIONZ™ Engine : Yes

Accessory Terminal : Multi Connector

Audio/Video Output(s) :Yes via Mutli-Use Connector

HD Output : Yes (1080i)

USB Port(s) : Yes - Supports USB 2.011

Operating System Compatibility : Microsoft® 2000 Professional, XP Home and Professional; Macintosh® OS 9.1/9.2/OS X (10.1-10.5)

Supplied Software : Windows: Picture Motion Browser Vers 3.0.02 + USB Driver

ISO : Auto / 80 / 100 / 200 / 400 / 800 / 1600 / 3200 / 64006

????????